

specifications 884 Eco Cushtex

| | |
|-------------------|---|
| style name | boxed sq |
| size | 50 cm x 50 cm |
| construction | integrated tufted pattern loop |
| yarn | 100% b.c.f. 6,0 nylon |
| dye method | solution dyed |
| guage | 1/10 |
| pile height | 5.0 mm |
| total thickness | 8.0 mm |
| pile weight | 26 oz per sq yd (884gm/m ²) |
| total weight | 136 oz per sq yd - 4,624gm/m ² |
| primary backing | polyester spunbonded |
| secondary backing | EcoGreenbac™ Recyclable Cushion |
| packing | 16 pcs / 4sqm per box |

performance

| | | |
|----------------------------|--|---------------------------|
| wear classifications | heavy contract use | |
| flammability tests | CRF: 6.7kw/m ² Smoke: 245% | AS/ISO 9239.1 |
| soil resistance | 8 of 10 passed | (3M test method) |
| colourfastness to light | greater than 4 | (AATCC 16E) |
| colourfastness to crocking | greater than 4 | (AATCC 165) |
| static load | min 85% recovery in 96 hour | |
| electrostatic propensity | less than 2.0 kv | (AATCC 134) |
| dimensional stability | less than 0.2% | (AACHEN test & DIN 54318) |
| antimicrobial test | pass | (AATCC 174) |
| compression test | pass | (ASTM D 1667) |

recommended installation method

