



Technical specifications

Eternal Original meets the requirements of EN-ISO 10582

	Total Thickness	EN - ISO 24346	2.0 mm
	Thickness wear layer	EN - ISO 24340	0.7 mm
	Collection size		26
	Commercial use	EN- ISO 10874	34 very heavy
	Industrial use	EN - ISO 10874	43 heavy
	Roll width	EN - ISO 24341	2.0 mm
	Roll Length	EN - ISO 24341	± 25 m
	Total weight	EN - ISO 23997	2.8 kg/m ²
	Dimension Stability	EN - ISO 23999	< 0.1%
	Residual indentation	EN - ISO 24343-1	≤ 0.05 mm
	Castor chair continuous use	EN 425	No effect
	Water tight installation	EN 13553	Yes
	Light fastness	EN - ISO 105 B-02	≥ 6
	Flexibility	EN - ISO 24344	ø 10mm
	Slip Resistance	DIN 51130	R10 - P3
	Chemical resistance	EN - ISO 26987	Very Good
	Electrical resistance	EN 1081 (R1)	R1 > 1.10 Ω
	Abrasion resistance	EN 660	Group T

All Eternal meets the requirement of EN 14014



	Reaction to fire	EN 13501-1	Bfl-s1
	Slip Resistance	EN 13893	DS - μ ≥ 0,30
	Body Voltage	EN 1815	< 2kV
	Thermal Conductivity	EN 12524	0.25 W/m-K

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

