

1-Component Hybrid Adhesive

UZIN KE 68 T

1-Comp. hybrid adhesive for floor and wall applications

MAIN APPLICATION FIELD:

- ▶ rubber floor coverings in tiles up to 4 mm (e.g. norament®)
- ▶ luxury vinyl tiles or design floors
- ▶ PVC and CV floor coverings in sheets and tiles
- ▶ linoleum in tiles up to 4 mm
- ▶ PVC wall cladding (e.g. Altro Whiterock, Gerflor Decochoc)

SUITABLE ON / FOR:

- ▶ absorbent and non absorbent substrates
- ▶ deformable or elastic substrates (e.g. underlays, wood, please obtain technical advice for metal)

Note: Also suitable for processing on the floor. Obtain technical advice for additional combinations of floor covering and substrates.



PRODUCT BENEFITS/FEATURES:

UZIN KE 68 T is a ready to use and user-friendly 1-comp. hybrid adhesive with very low emissions. The compact adjustment of the adhesive is ideal for floor and wall applications. The adhesive is very resistant against heavy loads, high temperatures or humidity. For interior use.

- ▶ ideal consistency for working on vertical surfaces
- ▶ for installers with PUR or epoxy sensitization
- ▶ for areas with high temperatures



TECHNICAL DATA:

Packaging	plastic bucket
Pack size	11 kg
Shelf life	min. 12 months
Colour, wet	beige
Colour, dry	beige
Consumption	250 - 2700 g/m ²
Working time	up to 40 minutes*
Minimum application temperature	15 °C at ground level
Loadable	after 24 hours*
Joint sealing	after 24 hours*
Final strength	after 3 - 5 days*

*At 20 °C and 65% relative humidity.



SUBSTRATE PREPARATION:

The substrate must be sound, load-bearing, dry, free from cracks and materials (dirt, oil, grease) that would impair adhesion. The surface must be free of dust and as even as possible. Test the substrate in accordance with applicable standard or notices and report any deficiencies.

The datasheets for other used products have to be observed.

APPLICATION:

1. Before use, allow the adhesive to come to room temperature. Pull off the foil cover after opening and remove any surface skin if necessary. Do not mix the skin in.
2. Apply an even coat of adhesive onto the wall using a suitable notched trowel. Do not apply more adhesive than can be laid with good transfer onto the back of the covering within the working time. Press down the covering well.
3. Remove residues while fresh with wipes from the UZIN Clean-Box. Hardened adhesive can only be removed mechanically.

CONSUMPTION INFORMATION:

For the adhesion of Altro Whiterock, Altro Debolon recommends a C2 trowel notch.

CONSUMPTION INFORMATION:

Coating/Backing	Toothing	Consumption approx.*
Smooth or slightly structured, e.g. PVC or LVT	A5	250 - 300 g/m ²
Structured, e.g. rubber	A2	350 - 400 g/m ²
Wood or engineered timber wall cladding	B3	900 - 1000 g/m ²
Rigid PVC wall cladding	C2	2500 - 2700 g/m ²

Observe the technical guidelines of the wall covering manufacturer.

IMPORTANT NOTES:

- ▶ A shelf life of 12 months when stored in moderately cool conditions, in the original packaging. Frost-resistant down to - 25 °C. Carefully and tightly reseal opened containers with the foil and use the contents quickly. Allow containers to come to room temperature before use.
- ▶ Best applied between 18 - 25 °C, with the floor temperature above 15 °C and relative air humidity below 65%. Low temperatures and low air humidity lengthen the working and drying time. Whilst high temperatures and high air humidity shorten the working and drying time.

- ▶ Humid substrates may cause secondary emissions and odours. Therefore, ensure the compound is dry before applying the adhesive.
- ▶ Installations onto substrates with old adhesive residues may cause interactions and lead to unpleasant odours. Ideally these should be removed completely. In all situations adhesive residues must be remedied via the use of primers and coatings of compound at least 3 mm thick.
- ▶ Before installing, the floor covering must be adequately acclimatised to the indoor climate and free from tension.
- ▶ Strong deformation of the roll ends, hanging bays, extremely raised edges or strong curvatures must be weighed down during the adhesion.
- ▶ Please check the adhesive recommendations (online) or obtain application advice when installing chlorine-free floor coverings.
- ▶ Follow the generally acknowledged rules of the trade and technology for the installation of floor covering in respective of the applicable national standards (e.g. EN, DIN, OE, SIA, etc.)

SEALS OF QUALITY & ECOLABELS:

- ▶ Solvent-free, containing methoxysilane
- ▶ EMICODE EC 1 PLUS / Very low emission
- ▶ DE-UZ 113 / Environmentally friendly because of low emissions

COMPOSITION:

Silane-terminated prepolymers, mineral fillers, additives.

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Solvent-free adhesive containing methoxysilane. Non flammable. Avoid contact with eyes and skin. When curing, produces traces of methanol. Ensure good ventilation during application. Wear protective gloves and safety-goggles. After contact with skin wash with plenty of water and soap. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Observe safety information on product label as well as safety data sheet. Once cured, has a neutral odour and presents no physiological or ecological risk

DISPOSAL:

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty, scraped and drip-free containers are recyclable. Containers with liquid residue, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste. Therefore collect waste material and allow to harden, then dispose as Construction Waste.